

AMERICAN TOOTH INDUSTRIES

1200 Stellar Drive • Oxnard, CA 93033-2404 • (805) 487-9868 Corporate e-mail: info@americantooth.com • www.americantooth.com

# SAFETY DATA SHEET

# 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

PRODUCT NAME	Pozzi Ortho Resin Liquid (All Colors)
Product Description	Methyl Methacrylate
Manufacturer	American Tooth Industries 1200 Stellar Drive Oxnard, CA 93033 805-487-9868 Emergency Phone Number: Infotrac: 800-352-5053
Recommended use	Pozzi Ortho Resin is a self-curing, high impact acrylic that was developed for orthodontic use in making strong and attractive appliances and retainers.
Restrictions on use	N/A
2. HAZARDS IDENTIFICATION	
Hazard classification	Flammable liquid Category 2. Skin corrosion / irritation Category 2. Skin sensitization Category 1.
	STOT- single exposure Category 3. Hazardous to the aquatic environment- Acute Hazard Category 3.
Signal Word	STOT- single exposure Category 3. Hazardous to the aquatic environment- Acute
Signal Word Hazard Statements	STOT- single exposure Category 3. Hazardous to the aquatic environment- Acute Hazard Category 3.
	<ul> <li>STOT- single exposure Category 3.</li> <li>Hazardous to the aquatic environment- Acute</li> <li>Hazard Category 3.</li> <li>Danger</li> <li>H225: Highly flammable liquid and vapor.</li> <li>H315: Causes skin irritation.</li> <li>H317: May cause an allergic skin reaction.</li> <li>H335: May cause respiratory irritation.</li> </ul>

#### **Precautionary statements**

P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical/ventilating/ lighting equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P261: Avoid breathing vapors.

P264: Wash thoroughly after handling.

P271: Use only outdoors or in a well-ventilated area.

P272: Contaminated work clothing should not be allowed.

P273: Avoid release to the environment P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303-P361+P353: IF ON SKIN (or hair): Remove/ take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

P370+P378: In case of fire, use water spray, foam, dry powder or CO2 for extinction.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in well-ventilated place. Keep cool.

P405: Store locked up.

P501: Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.

#### Other hazards

Prolonged or repeated exposure can cause liver and kidney damage and an allergic reaction to the skin.

# 3. COMPOSTITION/INFORMATION ON INGREDIENTS

Statement for unknown toxicity	N/A
Chemical name	Methyl Methacrylate
Common name/synonyms	Stabilized methyl methacrylate monomer, 2- propenoic acid, 2-methyl-, methyl ester; MMA; MMM
Impurities and stabilizing additives	Standard grades contain inhibitors from among the following: 800 ppm Maximum Hydroquinone (CAS No. 123-31-9) p-Methoxyphenol (CAS No. 150-76-5) 2, 4-Dimethyl-6-t-butylphenol (CAS No. 1879-09-0) Octadecyl 3,5-di-tert-butyl-4-hydroxycinnamate (CAS No. 2082-79-3) Phenotiazine (CAS No. 92-84-2)

Chemical Name	Weight - %	CAS Number
Methyl Methacrylate	90-100%	80-62-6
Other Esther Adducts	0.1-0.3%	Not required
Hydroquinone	0.0026-0.0029%	123-31-9

\*Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret is required.

# 4. FIRST AID MEASURES

# **Description of First Aid Measures**

Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell
Skin Contact	Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before re-use.
Eye Contact	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain immediate medical attention.

### Most important symptoms or effects, both acute and delayed:

Causes skin irritation. May cause respiratory irritation. May cause an allergic skin reaction.

### Indication of immediate medical attention and special treatment needed:

None necessary.	
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	In case of fire, use water spray, foam, dry powder or CO2 for extinction. Keep containers cool by spraying with water if exposed to fire.
Unsuitable extinguishing media	Do not use water jet.
Special hazards arising from substance	Highly flammable liquid and vapor. May polymerize on heating. Sealed containers may rupture explosively if hot.
Special protective equipment and Precautions for fire fighters	A self-contained breathing apparatus and suitable protective clothing should be worn in fire conditions.
6. ACCIDEDNTAL RELEASE MEASURE	ES
Personal precautions, protective equipment and emergency procedures	Eliminate source of ignition. Wear protective gloves and eye/face protection. Avoid vapors. See Section. 8.
Environmental precautions	Avoid release to the environment. Spillages or uncontrolled discharges into watercourses must be

Methods and materials for containment and cleaning up Coll

Collect spillage. Do not absorb onto sawdust or other combustible materials. Transfer to a container for disposal or recovery. Use only non-sparking tools.

alerted to the appropriate regulatory body.

### 7. HANDLING AND STORAGE

HandlingDo not eat, drink, or smoke at the work place.Wash thoroughly after handling. Avoid breathing<br/>vapors. Use only outdoors or in a well-ventilated

	area. The vapor is heavier than air; beware of pits and confined spaces.
Storage	Ground container and receiving equipment. Use explosion proof electrical equipment. Use only non- sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Store in well-ventilated place. Keep cool. Store locked up. Keep away from heat, sparks, open flame, hot surfaces- No smoking. Protect from sunlight. IMPORTANT: Methacrylates stored in bulk must be kept in contact with air (oxygen). Monomer vapors are uninhibited and may form polymers in vent or flame arresters, resulting in blockage of vents. Check inhibitor levels every 6 months and return to original level.
Storage temperature	Store at temperatures not exceeding 77°F (25°C).
Incompatible materials	Polymerization catalysts, such as peroxy or azo compounds, strong acids, alkalis and oxidizing agents, Oxides and salts of transition metals. Organic Nitrogen containing compounds. Cyclohexanone/cyclohexanol tautomer.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

OSHA Permissible Exposure Limits	410 mg/m3 TWA
ACGIH Threshold Limit Values	205 mg/m3 TWA
Other limitations recommended	N/A
Appropriate Engineering Controls	Do not eat, drink, or smoke at the work place. Provide adequate ventilation, including appropriate local extraction, to ensure that the occupational exposure limit is not exceeded. Consideration should be given to the work procedures involved and the potential extent of exposure as they may determine whether a higher level of protection is required.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color	Liquid Various colors including Pink, Clear, Trans. Pink, Red, Purple, Magenta, Orange, Flour. Yellow, Green, Turquoise, Blue, Black and Gold
Odor	Characteristic strong and acrid.
Odor Threshold (ppm)	0.5-1.0
pH	N/A
Melting Point (°C)	-48
Form 244 Rev 9/11/15	Page <b>5</b> of <b>9</b>

Initial Boiling Point(°C) Flash Point Evaporation Rate Flammability (solid, gas) Upper/Lower Flammability limits Vapor Pressure Vapor Density Solubility Partition Coefficient: n-octano/water Auto-ignition Temperature Decomposition Temperature Decomposition Temperature Uscosity Explosive Properties Oxidising Properties Density (g/ml) Minimum Ignition Energy (mJ)	100.5 10 [Closed cup] N/A N/A 12.5/2.1 3600 AT 68°F (20°C) 3.5 Slightly soluble. 1.6% at 68°F(20°C) 1.38 421 N/A N/A N/A N/A N/A N/A 0.949 at 60°F (15.5°C) 0.89-0.97 at 73.5°F (23°C)
Reactivity Chemical Stability Hazardous Reactions Conditions to avoid Materials to avoid Hazardous Decomposition Products	<ul> <li>Will exothermically polymerize in the presence of inhibitors.</li> <li>Stable in the presence of inhibitor.</li> <li>Susceptible to polymerization initiated by prolonged heating or at the presence of catalyst.</li> <li>Heat and direct sunlight.</li> <li>Polymerization catalysts, such as proxy or azo compounds, strong acids, alkalis and oxidizing agents. Oxidize and salts of transition metals.</li> <li>Organic Nitrogen containing compounds.</li> <li>Cyclohexanone/cyclohexanol tautomer</li> <li>Does not decompose up to auto-ignition temperature.</li> </ul>
11. TOXILOGICAL INFORMATION	
Acute Toxicity	
Inhalation Inhalation toxicity data Inhalation STOT- single exposure Respiratory sensitization data	May cause respiratory irritation. May cause drowsiness and dizziness. LC50 (vapor) 7093 ppm (29.8 mg/l) (4hr) Exposure to high concentrations may produce adverse effects on the nasal epithelium. Not a respiratory sensitizer. Irritant to the respiratory system and high concentrations may aggravate pre-existing conditions.
Ingestion Ingestion toxicity date Ingestion STOT- single exposure	Low oral toxicity, but ingestion may cause irritation of the gastrointestinal tract. LD 50 (oral) > 500mg/Kg N/A
Skin contact Skin contact toxicity data	May cause an allergic skin reaction. Causes skin irritation. Repeated and/or prolonged contact may cause dermatitis. LD50 (dermal) > 500 mg/Kg
Form 244 Rev 9/11/15	Page 6 of 9

Skin contact STOT- single exposure Skin sensitization data	N/A Skin sensitization has been reported in studies with guinea pigs. (OECD 406). Evidence of contact sensitization in man.
Eye contact Eye contact toxicity data EyeSTOT- single exposure	High vapor concentration will cause irritation. Slight irritant to rabbit eyes. (OECD 405) N/A
Germ cell mutagenicity data`	Salmonella typhimurium (TA1535, 1537, 97, 98, 100) negative (OECD 471)
Repeated exposure toxicity	Repeated exposure to high levels produces adverse effects on the heart, lungs, liver, and kidneys. Repeated exposure of animals by inhalation to levels at or above the occupational exposure level produces adverse effects on the nasal epithelium (levels of 100 and 400 ppm) There is no reason to believe that methyl methacrylate represents a carcinogenic or mutagenic hazard to man based upon evidence from well conducted animal studies, relevant mutagenicity studies and adequate epidemiology studies in relevant cohorts. Recent studies in animals have shown that high exposures do not produce embryo or foetotoxic nor teratogenic effects in the presence of maternal toxicity.
STOT- repeated exposure data	NOEL (oral) (rat) (104 weeks) >2000ppm NOAEC (inhalation) (rat) (104 weeks) 100 ppm (OECD 453) NOAEC (inhalation) (mouse) (14 weeks) 1000 ppm (OECD 412)
Reproductive toxicity	Teratogenic and feotoxiceffects only observed in presence of maternal toxicity. NOAEC (mouse) = 9000 ppm NOAEC (rat) > 2028 ppm
Carcinogenicity data	No evidence of carcinogenicity. (OECD 451)
Other information	None

# 12. ECOLOGICAL INFORMATION (If available)

Ecotoxicity	Low toxicity to fish. LC50 (fish) (typically) >100 mg/l LC50 (fathead minnow) (96 hour) (static) 130 mg/l Harmful to aquatic invertebrates. EC50 (Daphnia magma) (48 hour) 69 mg/l Low toxicity to algae. EC50 (selenastrum capricornutum) (86 hour) 170mg/l
-------------	---

	NOEC (zebra fish) (35 day) (flow through) 8.4 mg/l The product is substantially removed in biological treatment processes.
Persistence and degradability	Readily biodegradable. Chemical Oxygen Demand (COD): 88% (28 days) Inherent Biodegradation. Dissolved Organic Carbon Removal (DOC) removal): >95% (28 days)
Bioaccumulative potential	This product has low potential for bioaccumulation.
Mobility	The product is predicted to have high mobility in soil.
Other adverse effects	None known.

# 13. DISPOSAL CONSIDERATIONS (If applicable)

# Avoid release to the environment. Decontaminate empty drums before recycling.

Disposal methods Dispose of contents/container to hazardous waste in accordance with local, state or national legislation. Incinerate under approved controlled conditions, using incinerators suitable for the disposal of flammable organics.

# 14. TRANSPORT INFORMATION (If applicable)

UN No.	1247	
Proper Shipping Name	METHYL METHACRYLATE MONOMER, STABILIZED If material is shipped in quantities greater than 1000 lb. per container, the Proper Shipping Name is RQ METHYL METHACRYLATE MONOMER, STABILIZED	
Class	3	
Packing group	II	
Special precautions for user	No special requirements	
Transport in bulk according to Annex II of MARPOL73/78 and the IBC code N/A		
Reportable Quantity (RQ)	1000 lb	
TDG Class	3.2 (9.2)	
TMD Packing Group	II	
Form 244 Rev 9/11/15	Page <b>8</b> of <b>9</b>	

## 15. REGULATORY INFORMATION (If available)

#### **US Federal Regulations**

1000 lb Superfund reportable discharge Not listed SARA 302- Extremely Hazardous Substances SARA 311/312 Hazard Categories Acute Yes Chronic No Fire Yes Reactivity Yes Pressure No SARA 313- Toxic Chemicals

Listed.

#### **US State Regulations** California

Proposition 65 (California): Not listed

# **Canadian Regulations**

WHMIS Classification

Class B, Division 2, Flammable Liquid Class D, Division 2, Subdivision B, Toxic Material Class F, Dangerously Reactive Material

#### **NFPA** Rating

Health	2
Flammability	3
Reactivity	2

### **NPCA-HMIS** Rating

Health	2
Flammability	3

Reactivity 2

### **16. OTHER INFORMATION**

#### Date of Revision: 09/21/15

American Tooth Industries believes that the information and recommendations contained herein (including data and statements) are accurate as of date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of American Tooth Industries expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.

Form 244 Rev 9/11/15