Section 1- Chemical product and Company Identification

Proudct Material:	SILICONE RUBBER		
Product Name:	ZY-4451 (4411.4421.4431.4441.4461.4471.4481)		
Manufacture:	Dong Guan New-Orient Technology Co, Ltd		
Address: Long-he Industry, Tian Xin Village, Huang Ji		ang Jiang Town, Dong Guan	
Tel No.:	0769-83639068	Fax:	0769-83639098

Section 2-Composition/information on Ingredient

Chemical Name	Wt(%)	CAS No.
Methyl vinyl polysiloxane	58%~83%	68083-19-2
Silicone dioxide	13%~33%	112945-52-5
Silicone oil	4%~9%	63148-62-9

Section 3-Hazards Identification

	1.Health harm:	NO heavy metal、halogen、PAHS、16P
¥ 81 91 11	2.Environmetn harm:	N. A
Important information	3.Major symptom:	N. A
IIIIOIIIIatioii	4.Blast hazard:	N. A
	5.fataless style:	N. A

Section 4- First-Aid Measures

Different exposure methods or means of emergency protection 3	1.Skin:	Wash thoroughly with soap and water ,flush with plenty of water. Take off spoilt clothes. Seek medical attention in event of irritation
	2.Eyes:	Rinse immediately with plenty of water for 10 minutes at least . seek medical attention in event of irritation
	3.Inhalation:	If combustion products are inhaled, remove from contaminated area Other measures are usually not necessary, seek medical attention in event of irritation
	4.Ingestion:	After swallowing, give a cup of water immediately, first aid is not generally required, if in doubt, seek medical attention in event of irritation

Section 5-Fire Fighting Measures

1.Hazard speciality:	high temperature easy burn	-
2.Extinguishing agent:	carbon monoxide,carbon dioxide,dry chemical,foam or water fog	
3.Extinguishing notes:	N. A	

Section 6-Accidental Release Measures

Personal Attention:	NO special note
Environmetn Attention:	NO special note
Methods for cleaning up:	Sweep, cleaning

Section 7-Handling and Storage

1.Operation Notes:	NO special note
2.Storage note:	normal temperature(2327°C)

Section 8-Exposure controls, personal protection

1.Project control:	NO special note

2.Respiratory system protect	ection: NO special note					
3.Eye protection:	NO special note					
4.Body protection:	NO special note					
5.Hand protection:	wash hand	wash hand				
6.Ambulanceman protectio	on: NO special note	NO special note				
7.Other protection:	NO special note					
Section 9- Physical and Ch	nemical properties					
Color:	translucence					
Density:	1.11					
ignite temperature:	NA					
Solubility:	Soluble in benzene					
Major use :	rubber mixing of sillcon rubber	f 450 series, the full transparent and high anti tearing er is produced with Silica of air phase as raw material. It parts of foodstuff industry and medical industry. processing				
Section 10- Stability and R	Reactivity					
1.Stability:	stable					
2.Ban-conmpound substan	nce: oxidizer					
3.Conditions to avoid:	N.A	A				
4.Hazardous Decomposition Prouducts:	Combustion products: Silica, car carbon	bon dioxide and trace amounts of incomplete combustion of				
Section 11-Toxicological In	information					
1.Acute toxicity:	N, A					
3.Excitive:	N. A					
4. Allergenicity:	N. A					
5.Mutagenicity:	N. A					
6.Carcinogenicity:	N. A					
7.Subacute and chronic to	oxicity: N. A					
Section 12-Ecological Info	ormation					
1.Ecologic	cal toxicity:					
Environmental 2.Biology	Degradability:					
impact may be 3.Abiolog	ical Degradability:					
	Enrichment or biology accumulate propo	ety:				
environment 5.Other bad	d effect :	Combustion products: Silica, carbon dioxide and trace amounts of incomplete combustion of carbon				
Section 13- Disposal Con-	siderations					
1.Castoff kind:	☐danger Castoff	☐Industry solid castoff				

disposed compliance with the respective countries national regulations

2 Castoff treat method :

Section 14-transport information

packing method:	carton				
transport notes:	NO special note				
Section 15-Regulatory Infor	mation			五科技	
Regulatory information: N.A	λ.		14/10	1 3	FE .
Section 16- Additional Infor	mation		営元	X	£24
1.Make departmetn:	QC department	2.Make	b	品管部	HongYan
3.Make date:	2018.05.25	4.Approve	ed by:		TianYuWen